

# GOLdeye®

Your last stop for CCTV solution



## High Speedome Camera


**GEG160 - Min. Illumination: 1 Lux(F/1.6)**  
**GEG160X - Min. Illumination: 0.1 Lux(F/1.6)**

- Powerful 264X zoom
- 360° endless panning
- Max 400°/s speed at preset mode
- 128 Preset positions
- Auto - Flip (Automatically turn 180° when the camera tilts to its lower limits)
- Privacy zone masking function (8 zone)
  - Alarm on action
- Option : Day & Night operation W/Built-in D&N lens



Made in Korea

CE FC



**SPECIFICATIONS**

Model	GEG160	GEG160X
Image Sensor	1/4" COLOR SONY SUPER HAD CCD	1/4" COLOR SONY EXview HAD CCD
Min. Illumination	1 Lux(F/1.6)	0.1 Lux(F/1.6)
Day & Night	Electronic D&N	
Zoom	22X Optical, 12X Digital	
Pixel	410K	
Resolution	480TV-Line	
Focal Length	f=3.4 ~ 122.4mm	
Pattern	4 patterns(210sec ~ 2 hours : depends on complexity)	
Privacy Zone	8 zone	
Tour	8 tours	
Auto Scan	CW/CCW/Custom mode	
Pan Angle	360 deg(Endless)	
Tilt Angle	180 deg(Auto Flip)	
Pan/Tilt Speed	Manual : 0.05 ~ 120 deg/sec , Preset : Max. 400 deg/sec	
Endless Rotate	YES	
Digital Flip	YES	
Alarm Input	8	
Alarm Output	Open collector(5V DC, 40mA), Relay(2A 30VDC, 0.5A 125VAC)	
Address	255	
Remote Control	RS-485 or RS-422	
Protocol	AUTO(Pelco-D)	
Baud Rate	AUTO(2400/9600)	
Current Consumption	24V AC/18W 1.5A	
Operation Temp.	-10°C ~ 50°C	
Preservation Temp.	-20°C ~ 60°C	
Dimension	Ø220x251.9(H)mm	
Weight	Approx. 2.2kg	

Authorized Distributor: